

PowerRide 3

Three Phase, 8 to 50 kW

PowerRide 3 **On-Line**

PowerRide 3 **Stand-by/Fast Transfer**

**HID, Incandescent, Fluorescent, LED
Modular Design, Front Access, Small Footprint
U.L. Listed to UL924 Lighting and UL1778 UPS
Standard, by CSA**

The PowerRide 3 incorporates state of the art technology with PWM (Pulse Width Modulated), double conversion design for emergency lighting applications. When utility power fails, the Inverter provides uninterrupted output power to the emergency lighting circuits in compliance with UL924 Life Safety Code for 90 minutes of egress illumination.

The PowerRide 3 is the best design solution for emergency lighting power for a wide range of commercial and industrial applications.

KEY FEATURES of the PowerRide:

- Latest technology microprocessor controlled electronics with PWM (Pulse Width Modulated) design for true Sine Wave output
- Efficiency: 94% online / 98% standby / fast transfer
- Continuous self-diagnostic and self-testing system
- LCD backlit panel for comprehensive monitoring of power line conditions and Inverter status
- RS232 and RS485 Ports
- Optional remote monitoring, including the advanced Global Monitoring System (GMS)
- Optional Battery Tracker Monitoring System
- Sealed maintenance-free lead calcium batteries with 10 year prorated warranty
- Battery Exerciser
- Modular cabinet design for ease of installation, small footprint with shallow 18" depth, convenient front access.
- Generator Compatible



Typical installations:

Office Buildings, Factories,
Warehouses, Hospitals, Hotels,
Motels, Schools, Universities,
Shopping Centers, Airports,
Casinos, Military Installations,
Apartment Buildings,
Supermarkets,
Train & Bus Terminals



Electronic Cabinet

STANDARD FEATURES

- Back-lit LCD Display for monitoring
- RS 232 & RS 485 ports for metering, measuring and diagnostic.
- System pre-wired for optional Global Monitoring System (GMS)
- High Frequency PWM with Digital Signal Processing Technology
- Make Before Break Internal Maintenance Bypass Switch
- Input and Main Output Circuit Breaker
- Generator Compatible with Automatic Governor (Slew Rate 2Hz/sec.)
- Inverter Test Switch
- Battery Breaker
- Battery Management Software

PowerRide 3

Power Rating: 8, 12, 16, 20, 24, 32, 40 and 50 KW
(higher capacity available)

Input Voltage: 208Y/120 or 480Y/277 VAC (-20% to +15%)

Output Voltages: 208Y/120 or 480Y/277 VAC

Output Frequency (Inverter Operation): 60 Hz \pm 0.5 Hz

Voltage Regulation: \pm 3%, Regulated within CBEMA curve

Output Wave Form: Sine-Wave < 5% THD.

Efficiency: 94% online / 98% standby / fast transfer

Power Factor: Unity

Crest Factor: 3:1 Typical

Surge Protection: The inverter will protect itself and the load against surges as defined in ANSI/IEEE C62.41 Cat. A & B.

Isolation: Complete from line. Output neutral bonded to ground

Noise Isolation: -120 dB Common-Mode; -60 dB Transverse-Mode

Battery: 10 year pro rated maintenance-free (AGM) battery

Recharge Current: Conforms to UL Standards

External Battery: Provisions for hardwire connection of optional external battery cabinets or DC source.

Environmental:

Humidity: 0 - 95% RH w/ no condensation

Operating Temp: UPS: 0° to 40°C. (32°-104°F)
Battery: 20° to 25°C. (68°-77°F)

Storage Temp: -20° to 25°C. (-4° - 77°F)

Altitude: Up to 10,000 ft

Safety Agencies: CUL, CSA Listed UL1778, UL924

Cabinet Sizes:

Standard Cabinet Layout:
Inverter cabinets 39"W x 18"D x 68"H
battery cabinets 51"W x 30.5"D x 70"H

Standard Battery Back-up time is 90 minutes @ full load. Other back-up times are available - contact factory.

OPTIONS

- Secondary Auxiliary Circuit Breakers (up to 14 one-pole OCB's): Normally On, Normally Off, Normally Off w/ Delay, Trip Alarm
- Form 'C' Contacts (5), (N.O.)
- Secondary Normally On/Off Terminal Block selection
- Remote Status Panel Unit with Audible Alarm and Silence Switch
- Local Audible Alarm with Silence Switch
- Input Current Harmonic Filter, 10% & 5% (This option will not be offer with Secondary Auxiliary Circuit Breakers)
- Make Before Break External Maintenance Bypass Switch
- Main Input and/or Output Circuit Breaker (with custom KAIC)
- Built-in Secondary Distribution
- External Attachable Panelboard (30-42 poles)
- EMI Filter
- Input Transient Voltage Surge Suppressor (TVSS)
- Harmonic Tolerance (up to K-50)
- Battery Tracker: Wireless Battery Status Monitoring System
- Certified Seismic Bracket
- Extended Warranty and Service Plans
- Spare Part Kits Available
- **Global Monitoring System (GMS)**
 - Provide SNMP MIB to monitor & log UPS status
 - Auto-sense 10M/100M Fast Ethernet
 - Manage & configure via Telnet, Web Browser or NMS
 - Support TCP/IP, UDP, SNMP, Telnet, SNTP, PPP, HTTP, SMTP Protocol
 - Sending both of SNMP TRAP and Email for events notification.
 - Auto email daily Battery Backup history report (configurable)
 - Basic NetAgent: LAN or WIFI
 - Advance NetAgent: LAN, WIFI, Dial-up Modem, or GPRS Modem



Consult Factory for more features and choices of remote communication.

KW	INPUT - OUTPUT	Model Numbers	DC Volts	Total Weights (lbs)	
				Inverter Cab.	(Qty) Battery Cab.
8	208Y/120 - 208Y/120 480Y/277 - 480Y/277 480Y/277 - 208Y/120	PD010B05LHT3-VA PD010H09LHT3-VA PD010H05LHT3-VA	192	(1 Cabinet) 1083 lbs	39w x 18d x 68h (1 Cabinets) 1392 lbs
12	208Y/120 - 208Y/120 480Y/277 - 480Y/277 480Y/277 - 208Y/120	PD015B05LHT3-VA PD015H09LHT3-VA PD015H05LHT3-VA	192	(1 Cabinet) 1446 lbs	51W x 30.5D x 68H (1 Cabinets) 3224 lbs
16	208Y/120 - 208Y/120 480Y/277 - 480Y/277 480Y/277 - 208Y/120	PD020B05LHT3-VA PD020H09LHT3-VA PD020H05LHT3-VA	192	(1 Cabinet) 1679 lbs	51W x 30.5D x 68H (1 Cabinets) 3560 lbs
20	208Y/120 - 208Y/120 480Y/277 - 480Y/277 480Y/277 - 208Y/120	PD025B05LHT3-VA PD025H09LHT3-VA PD025H05LHT3-VA	288	(1 Cabinet) 1679 lbs	51W x 30.5D x 68H (1 Cabinets) 4545 lbs
24	208Y/120 - 208Y/120 480Y/277 - 480Y/277 480Y/277 - 208Y/120	PD030B05LHT3-VA PD030H09LHT3-VA PD030H05LHT3-VA	288	(1 Cabinet) 1719 lbs	51W x 30.5D x 68H (1 Cabinets) 4568 lbs
32	208Y/120 - 208Y/120 480Y/277 - 480Y/277 480Y/277 - 208Y/120	PD040B05LHT3-VA PD040H09LHT3-VA PD040H05LHT3-VA	312	(1 Cabinet) 2066 lbs	51W x 30.5D x 68H (2 Cabinets) 8664 lbs
40	208Y/120 - 208Y/120 480Y/277 - 480Y/277 480Y/277 - 208Y/120	PD050B05LHT3-VA PD050H09LHT3-VA PD050H05LHT3-VA	552	(1 Cabinet) 2463 lbs	51W x 30.5D x 68H (2 Cabinets) 8800 lbs
50	208Y/120 - 208Y/120 480Y/277 - 480Y/277 480Y/277 - 208Y/120	PD062B05LHT3-VA PD062H09LHT3-VA PD062H05LHT3-VA	552	(1 Cabinet) 2565 lbs	51W x 30.5D x 68H (3 Cabinets) 12700 lbs

* Total Weights are approximate.
Specifications are subject to change without prior notification.

